

PRODUCT REFERENCE: EVA 55/10

DESCRIPTION: Black masterbatch based on an ethylene vinyl acetate copolymer carrier system. It contains a high concentration of a general purpose furnace type carbon black. This product **does not** meet new food contact regulation 2007/19/EC and is therefore **not suitable** for any food contact application.

APPLICATIONS: EVA 55/10 is suggested for the pigmentation of a variety of polyolefin and polyamide materials, either by direct addition during injection moulding or extrusion, or by pre-compounding. The relatively high concentration of carbon black is valuable when a specified final level of carbon black is required.

ADDITION RATE: 3 to 5 % depending on application.

PIGMENT TYPE: General purpose furnace carbon black.

TYPICAL PROPERTIES:

Pigment content: 50%

Melt flow rate: 10 g/10 min. (190⁰ C/10 kg)

Bulk density: 720 kg.m⁻³

Moisture content: 0.4%

Packaging: EVA 55/10 is normally packed in 25kg polyvalve bags. It should be stored in a clean dry area.

For Health and Safety information, please refer to the appropriate COLLOIDS Material Safety Data Sheet.

This product information is based on our general experience and does not constitute a specification. Since many factors affect the use of our products, no warranty is given or implied with respect to this information or patent infringement. We do not accept liability for any loss or damage arising from the use of this information. All sales are subject to our Standard Terms and Conditions of Sale.

TDS EVA 55/10 - 02/04/09