

PRODUCT REFERENCE: M UN BLACK 12754

DESCRIPTION: **M UN BLACK 12754** is a high performance black masterbatch giving good colour strength in a wide variety of polymer systems. This product is designed to meet the new food contact regulation 2007/19/EC (April 2009).

APPLICATIONS: **M UN black 12754** is recommended for injection moulding, extrusion and compound applications requiring good colour strength with minimum masterbatch addition. It is compatible with LDPE, LLDPE, PE copolymers, PA, HDPE, PS, ABS, SAN, PVC and PP.

ADDITION RATE: 1 to 4 % depending on application.

PIGMENT TYPE: High strength furnace carbon black.

TYPICAL PROPERTIES:

Pigment content: 35%

Melt flow rate: 10 g/10 min. (190⁰ C/10 kg)

Bulk density: 800 kg.m⁻³

Packaging: **M UN BLACK 12754** is normally packed in 25kg polyvalve bags. It should be stored in a clean dry area.

For Health and Safety information, please refer to the appropriate COLLOIDS Material Safety Data Sheet.

This product information is based on our general experience and does not constitute a specification. Since many factors affect the use of our products, no warranty is given or implied with respect to this information or patent infringement. We do not accept liability for any loss or damage arising from the use of this information. All sales are subject to our Standard Terms and Conditions of Sale.

TDS M UN BLACK 12754 – 02/04/09