

## PRODUCT REFERENCE: PE 48/92F

**DESCRIPTION:** PE 48/92F is a high quality black masterbatch containing a small particle size furnace carbon black. It uses a specially developed carrier system based on low density polyethylene.

**APPLICATIONS:** High quality film and other moulded and extruded products requiring excellent dispersion quality and good resistance to UV degradation. It has been successfully used in film extrusion down to 15 micron thickness. This product is formulated to meet new food contact regulation 2007/19/EC (April 2009).

**ADDITION RATE:** 5 to 6 % for optimum UV protection, 3 to 6 % for general pigmentation.

**PIGMENT TYPE:** Small particle size furnace carbon black.

### TYPICAL PROPERTIES:

**Pigment content:** 40 %

**Melt flow rate:** 5 g/10 min. (190° C/10 kg)

**Bulk density:** 650 kg.m<sup>-3</sup>

**Packaging:** PE 48/92F is normally packed in 25kg polyvalve bags. It should be stored in a clean dry area.

For Health and Safety information, please refer to the appropriate COLLOIDS Material Safety Data Sheet.

This product information is based on our general experience and does not constitute a specification. Since many factors affect the use of our products, no warranty is given or implied with respect to this information or patent infringement. We do not accept liability for any loss or damage arising from the use of this information. All sales are subject to our Standard Terms and Conditions of Sale. TDS PE 48/92F – 24/04/09