

**PRODUCT REFERENCE: *E-TEC*® ABS 11368**

<b>PRODUCT REFERENCE:</b>	<b><i>E-TEC</i>® ABS 11368</b>
<b>DESCRIPTION:</b>	Permanently anti static ABS compound using a non – migratory additive system.
<b>APPLICATION:</b>	This product is designed to be extruded or moulded without dilution. Pigment masterbatches suitable for ABS can be used to add colour, but the effect on other properties should be confirmed by trials.
<b>TYPICAL PROPERTIES:</b>	
<b>Surface Resistance:</b>	10 <sup>9</sup> Ω
<b>Melt flow rate:</b>	53.2g/10 mins.( 220°C @ 10Kg )
<b>Bulk density:</b>	600 kg.m <sup>-3</sup>
<b>Packaging:</b>	<b>E-TEC ABS 11368</b> is normally packed in 25kg polyvalve bags. It should be stored in a clean dry area.

For Health and Safety information, please refer to the appropriate COLLOIDS Material Safety Data Sheet.

This product information is based on our general experience and does not constitute a specification. Since many factors affect the use of our products, no warranty is given or implied with respect to this information or patent infringement. We do not accept liability for any loss or damage arising from the use of this information. All sales are subject to our Standard Terms and Conditions of Sale.