

## **PRODUCT REFERENCE: *E-TEC*<sup>®</sup> PP 11357**

<b>DESCRIPTION:</b>	<i>E-TEC</i> <sup>®</sup> <b>PP 11357</b> is a permanently anti static polypropylene compound using a non- migratory additive system. The base polymer is a medium flow, high impact copolymer. This product is a natural colour compound designed to be extruded or moulded without dilution. Conventional pigment masterbatches suitable for PP can be used to add colour.
<b>APPLICATION:</b>	Sheet extrusion and injection moulding of components requiring permanent antistatic properties.
<b>TYPICAL PROPERTIES:</b>	
<b>Surface Resistance:</b>	10 <sup>9</sup> ohms
<b>Melt flow rate:</b>	5.0g/10 min. (230 <sup>o</sup> C / 2.16 kg)
<b>Bulk density:</b>	480kg.m <sup>-3</sup>
<b>Packaging:</b>	<i>E-TEC</i> <sup>®</sup> <b>PP 11357</b> is normally packed in 25kg polyvalve bags. It should be stored in a clean dry area.

For Health and Safety information, please refer to the appropriate COLLOIDS Material Safety Data Sheet.

This product information is based on our general experience and does not constitute a specification. Since many factors affect the use of our products, no warranty is given or implied with respect to this information or patent infringement. We do not accept liability for any loss or damage arising from the use of this information. All sales are subject to our Standard Terms and Conditions of Sale. *PACE*<sup>®</sup> and *E-TEC*<sup>®</sup> are registered Trademarks of Colloids Limited