




COLLOIDS
THE MAKERS OF MASTERBATCH

**FOR COSMETICS AND
PHARMACEUTICAL APPLICATIONS**



MASTERBATCH FOR COSMETICS AND PHARMACEUTICAL APPLICATIONS

In the highly competitive Cosmetic and Pharmaceutical markets packaging can be a unique differentiator. With Colloids help, packaging designers are able to create new and exciting effects to help influence consumer buying behaviour.

Cosmetics – Colloids offer a bespoke design service able to produce a full range of colour and special effects including pearlescent, multi-colour angle effects, edge-glow, luminescent, phosphorescent, fluorescent, metallic, speckled, stone, ceramic and marble.

Pharmaceutical – Whether selected from our standard colour range or specifically designed to meet technical requirements, Colloids understanding of the pharmaceutical industry will ensure that products are manufactured to consistent formulatory and regulatory standards.

Our well equipped analytical and colour laboratories allow us to quickly develop formulations during the conceptual phase of a project. We are then able to continually optimise products from the initial trial stages through to full commercialisation.



Contents

This document contains information about a selection of products which are regarded as the most popular Masterbatches for Cosmetic and Pharmaceutical Applications.

Simply click on the title of the Masterbatch you would like more information on.

Other grades are available on request and technical data sheets are available for all our products. For more information please contact the Colloids Sales Team on +44 (0) 151 546 9222.

PLEASE NOTE: The product information contained within this pdf is based on our general experience and does not constitute a specification. Since many factors affect the use of our products, no warranty is given or implied with respect to this information or patent infringement. We do not accept liability for any loss or damage arising from the use of this information.

All sales are subject to our standard terms and conditions of sale.

Bespoke Products	5	White Products	12
Additive Products	5	D-K® Environmental Range	
Black Products		D-K® 100	13
Speciality Film Masterbatch	6	D-K® 200 & D-K® 300	13
Speciality Universal	6	E-TEC® Conductive compounds	14
Speciality Polymer Specific	6		
Colour Products			
Yellow Masterbatch	7		
Orange Masterbatch	7		
Red Masterbatch	7		
Pink Masterbatch	8		
Violet Masterbatch	8		
Blue Masterbatch	8		
Turquoise Masterbatch	8		
Green Masterbatch	9		
Silver/Gold Masterbatch	9		
Beige/Ivory Masterbatch	9		
Grey Masterbatch	10		
Terracotta/Brown Masterbatch	10		
All Colours	11		

Table Reference Information

***Colour indication only:**

If an accurate match is required customer should always trial material in their own polymer base – samples available on request. Evaluation on colour to RAL and Pantone® reference is based on Masterbatch let down in LDPE at 2%.

****Heat Stability:** Maximum recommended processing temperature.

***** Light fastness of pigments:** Scale 1-8 assessed using "Blue Wool Scale", 8 denotes highest performance i.e. best resistance to fading.

****** Weather fastness of pigments:** 1-5 assessed using "International Gray Scale" 5 denotes highest performance i.e. lowest fading outdoors. Ratings 3 and below are not recommended for long-term outdoor use. Light and weather fastness relate to pigment performance only and rely on the appropriate polymer stabilisation system to be present. All declarations relating to heat stability, light fastness and weather fastness are based on a Masterbatch addition rate of 5% in LDPE .

*******Food contact:** 'Tick' means that the Masterbatch is generally accepted for food packaging application in most countries. For specific details please contact the Colloids sales office

*******EC 94/62:** 'Tick' means that the Masterbatch conforms to the new EC Packaging Directive which controls heavy metal content.



Colloids Limited Kirkby Bank Road, Knowsley Industrial Park North, Merseyside L33 7SY
Telephone: +44 (0) 151 546 9222 Fax: +44 (0) 151 545 4741 Email: sales@colloids.co.uk Web: www.colloids.co.uk

Bespoke products

For non standard applications Colloids can offer a rapid colour matching and formulation development service creating masterbatches specific to our customers needs.

Bespoke colours, including blacks and whites, can be engineered to encompass a whole range of effects and finishes for some of today's most demanding markets.

We can also develop and produce coloured and natural products incorporating differing functional properties such as antistatic, UV stability, mould release, antibacterial etc.

Formulations can also be designed to give defined physical performance characteristics using the latest pigment and polymer technologies. This includes special black, white and conductive products.

Our technical team continues to work closely with our customers to develop specific formulations.

This may involve improving product performance or offering solutions for new markets and applications.

Symbol Reference Guide

✓ = Suitable, * = Partial suitability, X = Not suitable

Additive products

GRADE	POLYMER BASE	DESCRIPTION	POLYMER COMPATIBILITY For other polymers please contact Colloids sales office						RECOMMENDED USE					COMMENTS
			PE	PP	PS	ABS	PA	PET	EXTRUSION FILM	EXTRUSION – PROFILE / SHEET	INJECTION MOULDING	BLOW MOULDING	COMPOUNDING	
AP 0170 LD	PE	PROCESS AID	✓	✓	X	X	X	X	✓	✓	✓	✓	✓	Prevents die build up and melt fracture
CL 4175 PE	PE	PURGING AGENT	NA	NA	NA	NA	NA	NA	✓	✓	✓	✓	✓	Efficient purging agent
SB 1423 PE	PE	SLIP/ANTIBLOCK	✓	✓	X	X	*	*	✓	✓	✓	✓	✓	Slow acting slip/antiblock properties
SB 6616 PE	PE	SLIP/ANTIBLOCK	✓	✓	X	X	*	*	✓	✓	✓	✓	✓	Slow acting slip/antiblock properties (higher loading)
SL 6948 PE	PE	SLIP	✓	✓	X	X	*	*	✓	✓	✓	✓	✓	Fast acting slip agent
ST 0860 PE	PE	ANTISTATIC	✓	✓	X	X	X	X	✓	✓	✓	✓	✓	Amine free antistatic agent
ST 1028 PS	PS	ANTISTATIC	X	X	✓	✓	X	X	✓	✓	✓	✓	✓	Highly concentrated for styrenic polymers

Black products

Speciality Film Masterbatches

GRADE	POLYMER BASE	POLYMER COMPATIBILITY							CARBON BLACK CONTENT	CARBON BLACK TYPE	FOOD CONTACT APPROVED *****	INCLUDES ANTIBLOCK?	RECOMMENDED USE			
		For other polymers please contact Colloids sales office											FILM EXTRUSION	OTHER EXTRUSION	INJECTION/BLOW MOULDING	COMPOUNDING
		PE	EVA	PP	PS, ABS	PA (Nylon)	PET	PVC								
PE 48/92F	PE	✓	*	✓	*	*	*	*	40%	Small particle furnace	✓	X	✓	✓	✓	✓
PE 48/101	PE	✓	*	✓	*	*	*	*	40%	High strength general purpose	✓	X	✓	✓	✓	✓

Speciality Universal Masterbatches

GRADE	POLYMER BASE	POLYMER COMPATIBILITY							CARBON BLACK CONTENT	CARBON BLACK TYPE	FOOD CONTACT APPROVED *****	INCLUDES ANTIBLOCK?	RECOMMENDED USE			
		For other polymers please contact Colloids sales office											FILM EXTRUSION	OTHER EXTRUSION	INJECTION/BLOW MOULDING	COMPOUNDING
		PE	EVA	PP	PS, ABS	PA (Nylon)	PET	PVC								
UN 53/20	Universal	✓	✓	✓	✓	✓	✓	✓	50%	High jet furnace	✓	X	✓	✓	✓	✓
M UN BLACK 12753	Universal	✓	✓	✓	✓	✓	✓	✓	50%	Special food contact compliant, high strength	✓	X	✓	✓	✓	✓
M UN BLACK 12754	Universal	✓	✓	✓	✓	✓	✓	✓	35%	Special food contact compliant, high strength	✓	✓	✓	✓	✓	✓

Speciality Polymer Specific and other Masterbatches

GRADE	POLYMER BASE	POLYMER COMPATIBILITY							CARBON BLACK CONTENT	CARBON BLACK TYPE	FOOD CONTACT APPROVED *****	INCLUDES ANTIBLOCK?	RECOMMENDED USE			
		For other polymers please contact Colloids sales office											FILM EXTRUSION	OTHER EXTRUSION	INJECTION/BLOW MOULDING	COMPOUNDING
		PE	EVA	PP	PS, ABS, PC/ABS	PA (Nylon)	PET	PVC								
PP 50/10	PP	X	X	✓	X	X	X	X	40%	Small particle furnace	✓	X	X	✓	✓	✓
M PS BLACK 12752E	PS	X	X	X	✓	X	X	X	40%	Special food contact compliant, high strength	✓	X	X	✓	✓	✓
M SAN BLACK 10767	SAN	X	X	X	✓	X	X	X	30%	High jet furnace	✓	X	X	✓	✓	✓
PACE ® PT 4778	PET	X	X	X	X	X	✓	X	30%	Small particle furnace	✓	X	X	✓	✓	✓

Colour products

Yellow Masterbatch

COLOUR	GRADE	CLOSEST PANTONE® REFERENCE *	CLOSEST RAL REFERENCE *	POLYMER COMPATIBILITY For other polymers please contact Colloids sales office				HEAT STABILITY **	LIGHT FASTNESS ***	FOOD CONTACT APPROVED *****	PACKAGING DIRECTIVE EC 94/62 *****	COMMENTS
				LLDPE	LDPE	HDPE	PP					
YELLOW	PE 48/2/2057F	3945C	1016	✓	✓	*	*	240°C	6/7	✓	✓	Greenest shade through to reddest shade standard heavy metal free yellows
	PE 48/2/2450F	107C	None	✓	✓	*	*	240°C	6/7	✓	✓	
	PE 48/2/2905F	N/A	N/A	✓	✓	✓	✓	240°C	7	✓	✓	
	PE 48/2/2904F	114C	1018	✓	✓	✓	✓	240°C	7	✓	✓	
	PE 48/2/2028F	1225C	1003	✓	✓	*	*	230°C	6	✓	✓	

Orange Masterbatch

COLOUR	GRADE	CLOSEST PANTONE® REFERENCE *	CLOSEST RAL REFERENCE *	POLYMER COMPATIBILITY For other polymers please contact Colloids sales office				HEAT STABILITY **	LIGHT FASTNESS ***	FOOD CONTACT APPROVED *****	PACKAGING DIRECTIVE EC 94/62 *****	COMMENTS
				LLDPE	LDPE	HDPE	PP					
ORANGE	PE 48/3/1902F	137C	1028	✓	✓	✓	✓	240°C	7	✓	✓	Yellowest shade through to reddest shade heavy metal free oranges
	PE 48/3/1900F	N/A	N/A	✓	✓	*	*	230°C	5	✓	✓	
	PE 48/3/1046F	1645C	None	✓	✓	✓	✓	240°C	5	✓	✓	

Red Masterbatch

COLOUR	GRADE	CLOSEST PANTONE® REFERENCE *	CLOSEST RAL REFERENCE *	POLYMER COMPATIBILITY For other polymers please contact Colloids sales office				HEAT STABILITY **	LIGHT FASTNESS ***	FOOD CONTACT APPROVED *****	PACKAGING DIRECTIVE EC 94/62 *****	COMMENTS
				LLDPE	LDPE	HDPE	PP					
RED	PE 48/4/5909F	N/A	N/A	✓	✓	✓	✓	260°C	7	✓	✓	Yellowest shade through to bluest shade heavy metal free reds
	PE 48/4/5557F	179C	None	✓	✓	✓	✓	240°C	5/6	✓	✓	
	PE 48/4/5020F	186C	None	✓	✓	✓	✓	240°C	4	✓	✓	
	PE 48/4/5330F	1795C	None	✓	✓	✓	✓	250°C	6	✓	✓	
	PE 48/4/5505F	187C	3031	✓	✓	*	*	240°C	6	✓	✓	
	PE 48/4/5500F	201C	3002	✓	✓	✓	✓	240°C	6	✓	✓	
	PE 48/4/5670F	209C	3004	✓	✓	✓	✓	240°C	6	✓	✓	

Pink Masterbatch

COLOUR	GRADE	CLOSEST PANTONE® REFERENCE *	CLOSEST RAL REFERENCE *	POLYMER COMPATIBILITY For other polymers please contact Colloids sales office				HEAT STABILITY **	LIGHT FASTNESS ***	FOOD CONTACT APPROVED *****	PACKAGING DIRECTIVE EC 94/62 *****	COMMENTS
				LLDPE	LDPE	HDPE	PP					
PINK	PE 48/4/5246F	1905C	None	✓	✓	✓	✓	270°C	7	✓	✓	Bluest shade through to yellowest shade heavy metal free pinks
	PE 48/4/5080F	176C	None	✓	✓	✓	✓	290°C	7	✓	✓	

Violet Masterbatch

COLOUR	GRADE	CLOSEST PANTONE® REFERENCE *	CLOSEST RAL REFERENCE *	POLYMER COMPATIBILITY For other polymers please contact Colloids sales office				HEAT STABILITY **	LIGHT FASTNESS ***	FOOD CONTACT APPROVED *****	PACKAGING DIRECTIVE EC 94/62 *****	COMMENTS
				LLDPE	LDPE	HDPE	PP					
VIOLET	PE 48/5/4022F	None	None	✓	✓	✓	✓	240°C	6	✓	✓	

Blue Masterbatch

COLOUR	GRADE	CLOSEST PANTONE® REFERENCE *	CLOSEST RAL REFERENCE *	POLYMER COMPATIBILITY For other polymers please contact Colloids sales office				HEAT STABILITY **	LIGHT FASTNESS ***	FOOD CONTACT APPROVED *****	PACKAGING DIRECTIVE EC 94/62 *****	COMMENTS
				LLDPE	LDPE	HDPE	PP					
LIGHT BLUE	PE 48/5/4535F	299C	None	✓	✓	✓	✓	290°C	8	✓	✓	Greenest shade through to reddest shade heavy metal free light blues
	PE 48/5/4012F	298C	None	✓	✓	✓	✓	280°C	8	✓	✓	
	PE 48/5/4300F	2915C	None	✓	✓	✓	✓	280°C	8	✓	✓	
MID BLUE	PE 48/5/4025F	2945C	None	✓	✓	✓	✓	290°C	8	✓	✓	Greenest shade through to reddest shade heavy metal free mid blues
	PE 48/5/4021F	None	None	✓	✓	✓	✓	290°C	8	✓	✓	
DARK BLUE	PE 48/5/4020F	2755C	None	✓	✓	✓	✓	290°C	8	✓	✓	Greenest shade through to reddest shade heavy metal free dark blues
	PE 48/5/4500F	None	None	✓	✓	✓	✓	300°C	8	✓	✓	
	PE 48/5/4656F	289C	None	✓	✓	✓	✓	240°C	7	✓	✓	

Turquoise Masterbatch

COLOUR	GRADE	CLOSEST PANTONE® REFERENCE *	CLOSEST RAL REFERENCE *	POLYMER COMPATIBILITY For other polymers please contact Colloids sales office				HEAT STABILITY **	LIGHT FASTNESS ***	FOOD CONTACT APPROVED *****	PACKAGING DIRECTIVE EC 94/62 *****	COMMENTS
				LLDPE	LDPE	HDPE	PP					
TURQUOISE	PE 48/5/4358F	N/A	N/A	✓	✓	✓	✓	280°C	8	✓	✓	

Green Masterbatch

COLOUR	GRADE	CLOSEST PANTONE® REFERENCE *	CLOSEST RAL REFERENCE *	POLYMER COMPATIBILITY For other polymers please contact Colloids sales office				HEAT STABILITY **	LIGHT FASTNESS ***	FOOD CONTACT APPROVED *****	PACKAGING DIRECTIVE EC 94/62 *****	COMMENTS
				LLDPE	LDPE	HDPE	PP					
LIGHT GREEN	PE 48/6/3000F	3245C	None	✓	✓	✓	✓	300°C	8	✓	✓	
MID GREEN	PE 48/6/3011F	7482C	None	✓	✓	*	*	240°C	6	✓	✓	Bluest shade through to yellowest shade heavy metal free mid greens
	PE 48/6/3450F	7482C	None	✓	✓	*	*	240°C	6	✓	✓	
	PE 48/6/3116F	N/A	N/A	✓	✓	✓	✓	260°C	7	✓	✓	
	PE 48/6/3012F	355C	None	✓	✓	*	*	240°C	6	✓	✓	
	PE 48/6/3800F	362C	None	✓	✓	*	*	230°C	6	✓	✓	
DARK GREEN	PE 48/6/3015F	316C	None	✓	✓	✓	✓	300°C	8	✓	✓	Bluest shade through to yellowest shade heavy metal free dark greens
	PE 48/6/3641F	N/A	N/A	✓	✓	*	*	240°C	6	✓	✓	
	PE 48/6/3510F	356C	None	✓	✓	*	*	230°C	6	✓	✓	
	PE 48/6/3600F	357C	None	✓	✓	*	*	220°C	8	✓	✓	
	PE 48/6/3888F	N/A	N/A	✓	✓	✓	✓	300°C	8	✓	✓	

Silver/Gold Masterbatch

COLOUR	GRADE	CLOSEST PANTONE® REFERENCE *	CLOSEST RAL REFERENCE *	POLYMER COMPATIBILITY For other polymers please contact Colloids sales office				HEAT STABILITY **	LIGHT FASTNESS ***	FOOD CONTACT APPROVED *****	PACKAGING DIRECTIVE EC 94/62 *****	COMMENTS
				LLDPE	LDPE	HDPE	PP					
SILVER	PE 48/7/7030F	877C	9023	✓	✓	✓	✓	300°C	8	✓	✓	
GOLD	PE 48/7/7171F	872C	None	✓	✓	✗	✗	200°C	7	✓	✓	

Beige/Ivory Masterbatch

COLOUR	GRADE	CLOSEST PANTONE® REFERENCE *	CLOSEST RAL REFERENCE *	POLYMER COMPATIBILITY For other polymers please contact Colloids sales office				HEAT STABILITY **	LIGHT FASTNESS ***	FOOD CONTACT APPROVED *****	PACKAGING DIRECTIVE EC 94/62 *****	COMMENTS
				LLDPE	LDPE	HDPE	PP					
BEIGE	PE 48/2/2097F	None	1001	✓	✓	✓	✓	300°C	8	✓	✓	Greenest shade through to reddest shade heavy metal free beiges
	PE 48/2/1266F	N/A	N/A	✓	✓	✓	✓	250°C	7/8	✓	✓	
IVORY	PE 48/2/9600F	N/A	N/A	✓	✓	✓	✓	300°C	7/8	✓	✓	Greenest shade through to reddest shade heavy metal free ivories
	PE 48/2/9035F	7401C	None	✓	✓	✓	✓	300°C	8	✓	✓	

Grey Masterbatch

COLOUR	GRADE	CLOSEST PANTONE® REFERENCE *	CLOSEST RAL REFERENCE *	POLYMER COMPATIBILITY For other polymers please contact Colloids sales office				HEAT STABILITY **	LIGHT FASTNESS ***	FOOD CONTACT APPROVED *****	PACKAGING DIRECTIVE EC 94/62 *****	COMMENTS
				LLDPE	LDPE	HDPE	PP					
GREY	PE 48/7/8368F	N/A	N/A	✓	✓	✓	✓	300°C	8	✓	✓	Darkest shade through to lightest shade heavy metal free greys
	PE 48/7/8035F	C. GRAY 7C	7046	✓	✓	✓	✓	300°C	8	✓	✓	
	PE 48/7/8899F	429C	None	✓	✓	✓	✓	300°C	8	✓	✓	
	PE 48/7/8760F	428C	7040	✓	✓	✓	✓	300°C	8	✓	✓	

Terracotta/Brown Masterbatch

COLOUR	GRADE	CLOSEST PANTONE® REFERENCE *	CLOSEST RAL REFERENCE *	POLYMER COMPATIBILITY For other polymers please contact Colloids sales office				HEAT STABILITY **	LIGHT FASTNESS ***	FOOD CONTACT APPROVED *****	PACKAGING DIRECTIVE EC 94/62 *****	COMMENTS
				LLDPE	LDPE	HDPE	PP					
TERRACOTTA	PE 48/8/1340F	174C	None	✓	✓	✓	✓	300°C	8	✓	✓	
MID BROWN	PE 48/8/1281F	161C	8011	✓	✓	✓	✓	300°C	8	✓	✓	
DARK BROWN	PE 48/8/1550F	None	None	✓	✓	✓	✓	300°C	8	✓	✓	Darkest shade through to lightest shade heavy metal free browns
	PE 48/8/1028F	476C	None	✓	✓	✓	✓	300°C	8	✓	✓	

All Colours

COLOUR	GRADE	CLOSEST PANTONE® REFERENCE *	CLOSEST RAL REFERENCE *	POLYMER COMPATIBILITY For other polymers please contact Colloids sales office				HEAT STABILITY **	LIGHT FASTNESS ***	FOOD CONTACT APPROVED *****	PACKAGING DIRECTIVE EC 94/62 *****	COMMENTS
				LLDPE	LDPE	HDPE	PP					
YELLOW	PE 48/2/2057F	3945C	1016	✓	✓	*	*	240°C	6/7	✓	✓	Greenest shade through to reddest shade standard heavy metal free yellows
	PE 48/2/2450F	107C	None	✓	✓	*	*	240°C	6/7	✓	✓	
	PE 48/2/2905F	N/A	N/A	✓	✓	✓	✓	240°C	7	✓	✓	
	PE 48/2/2904F	114C	1018	✓	✓	✓	✓	240°C	7	✓	✓	
	PE 48/2/2028F	1225C	1003	✓	✓	*	*	230°C	6	✓	✓	
ORANGE	PE 48/3/1902F	137C	1028	✓	✓	✓	✓	240°C	7	✓	✓	Yellowest shade through to reddest shade heavy metal free oranges
	PE 48/3/1900F	N/A	N/A	✓	✓	*	*	230°C	5	✓	✓	
	PE 48/3/1046F	1645C	None	✓	✓	✓	✓	240°C	5	✓	✓	
RED	PE 48/4/5909F	N/A	N/A	✓	✓	✓	✓	260°C	7	✓	✓	Yellowest shade through to bluest shade heavy metal free reds
	PE 48/4/5557F	179C	None	✓	✓	✓	✓	240°C	5/6	✓	✓	
	PE 48/4/5020F	186C	None	✓	✓	✓	✓	240°C	4	✓	✓	
	PE 48/4/5330F	1795C	None	✓	✓	✓	✓	250°C	6	✓	✓	
	PE 48/4/5505F	187C	3031	✓	✓	*	*	240°C	6	✓	✓	
	PE 48/4/5500F	201C	3002	✓	✓	✓	✓	240°C	6	✓	✓	
	PE 48/4/5670F	209C	3004	✓	✓	✓	✓	240°C	6	✓	✓	
PINK	PE 48/4/5246F	1905C	None	✓	✓	✓	✓	270°C	7	✓	✓	Bluest shade through to yellowest shade heavy metal free pinks
	PE 48/4/5080F	176C	None	✓	✓	✓	✓	290°C	7	✓	✓	
VIOLET	PE 48/5/4022F	None	None	✓	✓	✓	✓	240°C	6	✓	✓	
LIGHT BLUE	PE 48/5/4535F	299C	None	✓	✓	✓	✓	290°C	8	✓	✓	Greenest shade through to reddest shade heavy metal free light blues
	PE 48/5/4012F	298C	None	✓	✓	✓	✓	280°C	8	✓	✓	
	PE 48/5/4300F	2915C	None	✓	✓	✓	✓	280°C	8	✓	✓	
MID BLUE	PE 48/5/4025F	2945C	None	✓	✓	✓	✓	290°C	8	✓	✓	Greenest shade through to reddest shade heavy metal free mid blues
	PE 48/5/4021F	None	None	✓	✓	✓	✓	290°C	8	✓	✓	
DARK BLUE	PE 48/5/4020F	2755C	None	✓	✓	✓	✓	290°C	8	✓	✓	Greenest shade through to reddest shade heavy metal free dark blues
	PE 48/5/4500F	None	None	✓	✓	✓	✓	300°C	8	✓	✓	
	PE 48/5/4656F	289C	None	✓	✓	✓	✓	240°C	7	✓	✓	
TURQUOISE	PE 48/5/4358F	N/A	N/A	✓	✓	✓	✓	280°C	8	✓	✓	
LIGHT GREEN	PE 48/6/3000F	3245C	None	✓	✓	✓	✓	300°C	8	✓	✓	
MID GREEN	PE 48/6/3011F	7482C	None	✓	✓	*	*	240°C	6	✓	✓	Bluest shade through to yellowest shade heavy metal free mid greens
	PE 48/6/3450F	7482C	None	✓	✓	*	*	240°C	6	✓	✓	
	PE 48/6/3116F	N/A	N/A	✓	✓	✓	✓	260°C	7	✓	✓	
	PE 48/6/3012F	355C	None	✓	✓	*	*	240°C	6	✓	✓	
	PE 48/6/3800F	362C	None	✓	✓	*	*	230°C	6	✓	✓	

DARK GREEN	PE 48/6/3015F	316C	None	✓	✓	✓	✓	300°C	8	✓	✓	Bluest shade through to yellowest shade heavy metal free dark greens
	PE 48/6/3641F	N/A	N/A	✓	✓	*	*	240°C	6	✓	✓	
	PE 48/6/3510F	356C	None	✓	✓	*	*	230°C	6	✓	✓	
	PE 48/6/3600F	357C	None	✓	✓	*	*	220°C	8	✓	✓	
	PE 48/6/3888F	N/A	N/A	✓	✓	✓	✓	300°C	8	✓	✓	
SILVER	PE 48/7/7030F	877C	9023	✓	✓	✓	✓	300°C	8	✓	✓	
GOLD	PE 48/7/7171F	872C	None	✓	✓	X	X	200°C	7	✓	✓	
BEIGE	PE 48/2/2097F	None	1001	✓	✓	✓	✓	300°C	8	✓	✓	Greenest shade through to reddest shade heavy metal free beiges
	PE 48/2/1266F	N/A	N/A	✓	✓	✓	✓	250°C	7/8	✓	✓	
IVORY	PE 48/2/9600F	N/A	N/A	✓	✓	✓	✓	300°C	7/8	✓	✓	Greenest shade through to reddest shade heavy metal free ivories
	PE 48/2/9035F	7401C	None	✓	✓	✓	✓	300°C	8	✓	✓	
GREY	PE 48/7/8368F	N/A	N/A	✓	✓	✓	✓	300°C	8	✓	✓	Darkest shade through to lightest shade heavy metal free greys
	PE 48/7/8035F	C. GRAY 7C	7046	✓	✓	✓	✓	300°C	8	✓	✓	
	PE 48/7/8899F	429C	None	✓	✓	✓	✓	300°C	8	✓	✓	
	PE 48/7/8760F	428C	7040	✓	✓	✓	✓	300°C	8	✓	✓	
TERRACOTTA	PE 48/8/1340F	174C	None	✓	✓	✓	✓	300°C	8	✓	✓	
MID BROWN	PE 48/8/1281F	161C	8011	✓	✓	✓	✓	300°C	8	✓	✓	
DARK BROWN	PE 48/8/1550F	None	None	✓	✓	✓	✓	300°C	8	✓	✓	Darkest shade through to lightest shade heavy metal free browns
	PE 48/8/1028F	476C	None	✓	✓	✓	✓	300°C	8	✓	✓	

White products

GRADE	POLYMER BASE	POLYMER COMPATIBILITY							PIGMENT LOADING, equivalent to TiO ₂ content	INCLUDES ANTIBLOCK ?	RECOMMENDED USE					COMMENTS
		For other polymers please contact Colloids sales office									EXTRUSION FILM	EXTRUSION – PROFILE / SHEET	INJECTION MOULDING	BLOW MOULDING	COMPOUNDING	
		PE	PP	PS	ABS	PA	PET	PVC								
PE 48/1/12F	PE	✓	✓	*	X	*	✓	*	60%	X	✓	✓	✓	✓	✓	High quality - ideal for thin gauge film
PE 48/1/15F	PE	✓	✓	*	X	*	✓	*	50%	✓	✓	✓	✓	✓	✓	For medium gauge film with good antiblock properties
PE 48/1/47F	PE	✓	✓	*	X	*	✓	*	75%	X	✓	✓	✓	✓	✓	High quality and high pigment concentration
PE 48/1/49F	PE	✓	✓	*	X	*	✓	*	70%	X	✓	✓	✓	✓	✓	High quality and high pigment concentration
M PE WHITE 13749	PE	✓	✓	*	X	*	✓	*	70%	✓	✓	✓	✓	✓	✓	High quality and high pigment concentration including antiblock
M PS WHITE 12835	PS	X	X	✓	*	X	X	X	50%	X	X	✓	✓	X	✓	High quality white for a variety of applications including EPS
UN 53/1/03	Universal	✓	✓	✓	*	*	✓	*	75%	X	✓	✓	✓	✓	✓	High strength for diverse applications

D-K® Environmental Range

D-K® 100

The **D-K® 100** range consists of pro-degradant additive masterbatches developed by Colloids. These products are designed to cause conventional polyolefins to degrade and disintegrate whilst having minimal effect on initial polymer products or processing conditions.

D-K® 100 products are primarily intended for use in polyethylene film but can also be used in other polyolefin articles. Ideally such products should be used in applications where the degradation properties give a functional benefit in the finished piece. Such applications may include mulch film, rubbish bags, 'throw away' packaging etc.

D-K® 100 formulations have European food contact approval and, if colour is required, should be used in conjunction with Colloids range of **standard colour masterbatches for film** and **bespoke colours**.

D-K® 200 and D-K® 300

Colloids **D-K® 200** and **D-K® 300** product ranges both consist of a selection of colours based on polymers which are biodegradable and compostable.

The **D-K® 200** range is designed to be used in flexible applications such as carrier bags and caddy bin liners. The **D-K® 300** range is designed for use in rigid applications such as food packaging and personal care products.

The two ranges are designed for use in compostable polymers with the same or similar composition to the masterbatch base. Both base polymers are certified EN 13432 ('Requirements of packaging recoverable through composting and biodegradation') and DIN CERTCO biodegradable and compostable when used at the designated thickness.

The pigments incorporated in the masterbatches have all been carefully selected to meet EN 13432 specified element levels in the final packaging.

For further technical information or samples please contact the Colloids sales office.

E-TEC® Conductive compounds

GRADE	POLYMER TYPE	DESCRIPTION	APPLICATIONS					TYPICAL SURFACE RESISTIVITY
			EXTRUSION FILM	EXTRUSION SHEET	EXTRUSION PROFILE	INJECTION MOULDING	BLOW MOULDING	
E-TEC® ABS 11368	ABS	Colourless permanently antistatic compound which can be coloured with Colloids standard masterbatches	X	✓	✓	✓	X	10 ⁹
E-TEC® HD 12491	HDPE	Black conductive compound based on high molecular weight HDPE for blow moulded containers	X	✓	X	X	✓	10 ⁴
E-TEC® PE 4329	Modified LDPE	Black conductive compound designed for film extrusion down to 75 microns	✓	✓	✓	✓	X	10 ³
E-TEC® PP 11357	PP	Colourless permanently antistatic compound which can be coloured with Colloids standard masterbatches	X	✓	✓	✓	X	10 ⁹
E-TEC® PS 13731	Modified PS	Black conductive compound giving good gloss and low shrinkage	X	X	X	✓	X	10 ⁵